

SAFETY DATA SHEET

Identification Omega Cement Board

Exterior use.

Recommended useUse in accordance with manufacturer's recommendations.

Manufacturer Information

Company name: Omega Manufacturing Limited

Address: 19A David Blake Street

O'Meara Industrial Estate, Arima

Trinidad & Tobago

Website: www.omegamanufactruing.co info@omegamanufactruing.co

Phone: 868-646-0436

1. Hazard(s) Identification

Physical Hazards Not classified. N/A

Health Hazards Skin corrosion/irritation Category 2

Serious eye damage/ eye irritation Category 1
Sensitization, skin Category 1
Carcinogenicity Category 1A

Specific target organ toxicity, single exposure Category 3 -

(restrictory tract, irritation)

Hazard statement Causes skin irritation. Causes serious eye damage. May cause

an allergic skin reaction. May cause cancer. May cause

respiratory irritation.

Storage Store in a well-ventilated place.

Disposal Dispose of in accordance with local/regional/national/

international regulations.

Hazard(s) not otherwise

Classified (HNOC)

None known.

Supplemental information Not applicable.

2. Composition/information on ingredients

Chemical name	CAS number	%
Portland cement	65997-15-1	< 50
Silica Sand	14808-60-7.	< 50
Basalt Fiber	65997-17-3	<1.5
Continuous filament glass fiber	65997-17-3	<5

Note: Does not contain Asbestos, Cellulose Fibers or VOC's.

3. First-aid Measures

Inhalation	Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.
Skin contact	Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.
Eye contact	Dust in eyes: Flush with cold tap water for at least 15 minutes. If irritation persists, seek medical attention immediately.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms /effects, acute and delayed	May cause chemical eye burns. Permanent eye damage Including blindness could result. Dust may cause skin, eye, throat And respiratory system irritation and coughing.
Indication of immediate medical attention and	Provide general supportive measures and treat symptomatically.

General Information

special treatment needed

Ensure that medical personnel are aware of the material(s)

involved.

4. Fire-fighting Measures

Suitable extinguishing Use fire-extinguishing media appropriate for surrounding media materials.

Unsuitable extinguishing Media

Not applicable.

Specific hazards arising from the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/ instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods

Cool material exposed to heat with water spray and remove it if no risk is involved.

General fire hazards

No unusual fire or explosion hazards noted.

Precautions for safe handling

Use work methods which minimize dust production. Avoid inhalation of dust and contact with skin and eyes. Wash hands after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any Incompatibilities

Store all Ωmega Panels flat. Store in an enclosed materials shelter providing protection from damage and exposure to the elements. No specific clean-up procedure noted. For waste disposal, Avoid discharge to drains, sewers, and other water systems.

5. Individual Protection Measures, such as Personal Protective Equipment

Respiratory protection If engineering controls do not maintain airborne concentrations

below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been

established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to

control exposure

Skin Protection

Normal work clothing (long sleeved shirts and long pants are

recommended.

Hand Protection Repeated skin contact use suitable protective gloves.

Eye/face protection Wear approved safety goggles.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical

surveillance requirements. it is a good industrial hygiene practice to

minimize skin contact.

6. Appearance

Physical state: Solid

Form: Board Color: Grey

Odor: Low to no odor

Odor threshhold: Not applicable.

Ph: 12

Melting point/

freezing point: Not applicable.

Initial boiling point

and boiling range: Not applicable.

Flash point: Not applicable.

Evaporation rate: Not applicable.

Flammability (solid, gas): Not applicable.

- Upper/lower flammability or explosive limits.

Flammability limit – lower (%): Not applicable.
Flammability limit – upper (%): Not applicable.

Explosive limit – lower (%): Not applicable. Explosive limit – upper (%): Not applicable.

Vapor pressure: Not applicable.
Vapor density: Not applicable.

Relative density: 1.3 - 1.4

Solubility(ies)

Solubility (water): Insoluble

Partition coefficient: Not applicable.

Auto-ignition temperature: Not applicable.

Decomposition temperature: Not applicable.

Viscosity: Not applicable.

Bulk density: 1300 -1400Kg/m³

Explosive properties: Not explosive. **Oxidizing properties:** Not oxidizing.

VOC: 0%

7. Stability and Reactivity

Reactivity The product is stable and non-reactive under normal

conditions of use, storage and transport.

Chemical Stability Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Calcium oxides. Sulphur oxides.

8. Toxicological Information

- Information on likely routes of exposure.

Inhalation: Inhalation of dusts may cause respiratory irritation. Prolonged

and repeated exposure to airborne irreparable crystalline

silica can cause silicosis and/or lung cancer.

Skin contact: Dust can be irritating to skin.

Eye contact: Causes serious eye damage.

Ingestion: Ingestion may cause irritation and stomach discomfort.

Symptoms related to the physical, Chemical and toxicological Characteristics: May cause chemical eye burns. Permanent eye damage or blindness could result. Dust may irritate eyes, skin, throat and

upper respiratory system and cause coughing.

- Information on toxicological effects.

Acute toxicity: Not expected to be a hazard under normal conditions of

intended use.

Skin corrosion/irritation: Causes skin irritation. Dust can cause skin Irritation.

Serious eye damage/eye

Irritation:

Causes serious eye damage.

- Respiratory or skin sensitization.

Respiratory sensitization: Not a sensitizer.

Skin sensitization: Trace amounts of Cr(VI) compounds from Portland Cement

may cause allergic skin reaction even after one exposure.

Germ cell mutagenicity: No data available to indicate product or any components

present at greater than 0.1% are mutagenic or genotoxic.

9. Ecological information

- Ecotoxicity

Bio-accumulative potential: Bioaccumulation is not expected.

Mobility in soil: No data available.

Persistence and degradability: No data is available on the biodegradability of this product.

Other adverse effects: None expected.

10. <u>Disposal considerations</u>

- Disposal instructions

Local disposal regulations: Dispose of in accordance with local regulations.

Hazardous waste code: Not regulated.

Waste from residues/ Dispose of in accordance with local regulations. Not regulated

unused Products: as dangerous goods.

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.